

# UNSHIELDED TWISTED PAIR ACTIVE VIDEO RECEIVER – TYPE TR560

---

## TECHNICAL SPECIFICATIONS

## SECURITY SYSTEM

### DIVISION 16 – ELECTRICAL

### SECTION 16 \_\_\_ - CLOSED CIRCUIT TELEVISION (CCTV) SYSTEM

## PART 2 – PRODUCTS

### 2.1 GENERAL

- 2.1.1 All equipment to be supplied under this specification shall be new and the current model of a standard product of an OEM of record. An OEM of record shall be defined as a company whose main occupation is the manufacture for sale of the equipment supplied and which:
- A. Maintains a factory production line for the item submitted.
  - B. Maintains a stock of replacement parts for the item submitted.
  - C. Maintains engineering drawings, specifications, and operating manuals for the items submitted.
  - D. Has published and distributed descriptive literature and equipment specifications on the items of equipment submitted.
- 2.1.2 Specifications of equipment as set forth herein are salient and minimum requirements, unless otherwise stated and shall not be construed as limiting the overall quality, quantity or performance characteristics of items furnished.
- 2.1.3 Systems and components shall have been thoroughly tested and proven in actual use.
- 2.1.4 All systems and components shall be provided with the availability of a toll free (U.S. and Canada) technical support number from the manufacturer. The number shall provide technical assistance for either the dealer/installer or the end user at no charge

### 2.2 SPECIFICATIONS

- 2.2.1 The Twisted pair active video receiver, shall be a NITEK Model TR560 or approved equivalent, and shall be capable of receiving baseband type monochrome or color video signals over unshielded twisted pair (UTP) telephone cables, Category 3 or better, 24 gage or heavier up to a maximum cable length of 3,000 feet (900 meters), when connected to any NITEK Passive Video Transceiver (or approved equivalent at the opposite end of the UTP).
- 2.2.2 The Twisted pair active video receiver, shall be capable of receiving baseband type monochrome or color video signals over cables as specified in paragraph 2.2.1 to a maximum cable length of 6,000 feet (1,800 meters), when connected to a NITEK Model TT560 active Video Transmitter (or approved equivalent) at the opposite end of the UTP.
- 2.2.3 Receiving video signals, as described in paragraph 2.2.1 and 2.2.2 shall mean that the active video receiver shall be capable of delivering a monochrome or color video signal of 525 lines at the maximum specified distances.
- 2.2.4 The active receiver shall be provided with a power supply, which shall have provisions to plug directly into a 120 VAC wall outlet and shall provide an output voltage within the specifications of paragraph 2.3F. Output voltage shall be provided over two appropriate gauge wires (2 foot minimum length) for connection to the receiver power input terminals.

## UNSHIELDED TWISTED PAIR ACTIVE VIDEO RECEIVER – TR560

---

### TECHNICAL SPECIFICATIONS

### SECURITY SYSTEM

#### DIVISION 16 – ELECTRICAL

#### SECTION 16 \_\_\_ - CLOSED CIRCUIT TELEVISION (CCTV) SYSTEM

#### PART 2 – PRODUCTS (continued)

##### 2.2 SPECIFICATIONS (continued)

- 2.2.5 The active receiver shall provide frequency equalization by means of eight dual in-line (DIP) switches. The switches shall provide compensation for varying cable lengths from 100 to 3,000 feet, when a NITEK passive transmitter (or approved equivalent) is used and from 500 to 6,000 feet when a NITEK TT560 active transmitter is used. The effect of the frequency compensation shall be to both equalize and to amplify the video signal thereby providing loss compensation for video as cable length is increased.
- 2.2.6 The active receiver shall be capable of equalizing a color video signal of NTSC standard 525 lines or PAL standard 625 lines and shall deliver a baseband video signal capable of driving a 75 ohm impedance load.
- 2.2.6 The active receiver shall have built-in transient protection, with a screw connection for earth ground.
- 2.2.7 Video connection to the active receiver shall be by means of a BNC type female connector. A five screw terminal block shall provide connection to the UTP cable (2), 12 VDC power supply (2) and earth ground (1).
- 2.2.8 The active receiver shall also operate as specified in paragraph 2.2.1 when used as a receiver for any commercially available UTP equipped camera, camera enclosure and/or dome in which a NITEK Model VB24 (or approved equivalent) is installed as a transmitter device.
- 2.2.9 The active receiver shall operate within specifications without causing interference or interfering with any other base band video, communication, data and/or other low-voltage signals operating in multi-twisted pair UTP cables as specified in paragraph 2.2.1 or 2.2.2.
- 2.2.10 The active receiver shall be covered by a Limited Two Year Warranty.

##### 2.3 PERFORMANCE SPECIFICATIONS

- 2.3.1 The active receiver unit shall meet or exceed the following performance specifications:
- A. With a symmetrical and balanced composite input from the transmitter unit and using cables as specified in paragraph 2.2.1, at a cable length of 3,000 feet, the output shall be a 1 Vpp composite video signal into 75 ohms.
  - B. With a symmetrical and balanced composite input from the transmitter unit and using cables as specified in paragraph 2.2.2, at a cable length of 6,000 feet, the output shall be a 1 Vpp composite video signal into 75 ohms.
  - C. The receiver unit shall be capable of receiving RS170, NTSC, PAL, SECAM and CCIR video formats (color or monochrome).

**UNSHIELDED TWISTED PAIR ACTIVE VIDEO RECEIVER – TR560**

---

**TECHNICAL SPECIFICATIONS**

**SECURITY SYSTEM**

**DIVISION 16 – ELECTRICAL**

**SECTION 16 \_\_\_ - CLOSED CIRCUIT TELEVISION (CCTV) SYSTEM**

**PART 2 – PRODUCTS (continued)**

**2.3 PERFORMANCE SPECIFICATIONS (continued)**

- D. Operating frequency range: DC to 10 MHz.
- E. Common mode rejection to be > 70 dB.
- F. Voltage requirements: 12 to 24 VAC or DC (Power Supply provided).
- G. Size: Enclosure to be Black Cycolac ABS Flame Retardent Thermoplastic with a maximum size of 1.25”h x 1.5”w x .75”d (w = 2.25” including BNC connector).
- H. Temperature: System must operate in an ambient temperature of –40 Degrees C to +85 degrees C, 0 to 98% non-condensing.