

UNSHIELDED TWISTED PAIR ACTIVE VIDEO RECEIVER – TYPE TR515

TECHNICAL SPECIFICATIONS

SECURITY SYSTEM

DIVISION 16 – ELECTRICAL

SECTION 16 _ _ _ - CLOSED CIRCUIT TELEVISION (CCTV) SYSTEM

PART 2 – PRODUCTS

2.1 GENERAL

- 2.1.1 All equipment to be supplied under this specification shall be new and the current model of a standard product of an OEM of record. An OEM of record shall be defined as a company whose main occupation is the manufacture for sale of the equipment supplied and which:
 - A. Maintains a factory production line for the item submitted.
 - B. Maintains a stock of replacement parts for the item submitted..
 - C. Maintains engineering drawings, specifications, and operating manuals for the items submitted.
 - D. Has published and distributed descriptive literature and equipment specifications on the items of equipment submitted.
- 2.1.2 Specifications of equipment as set forth herein are salient and minimum requirements, unless otherwise stated and shall not be construed as limiting the overall quality, quantity or performance characteristics of items furnished.
- 2.1.3 Systems and components shall have been thoroughly tested and proven in actual use.
- 2.1.4 All systems and components shall be provided with the availability of a toll free (U.S. and Canada) technical support number from the manufacturer. The number shall provide technical assistance for either the dealer/installer or the end user at no charge

2.2 SPECIFICATIONS

- 2.2.1 The Twisted pair active video receiver, shall be a Northern Information Technology, Inc. (NITEK) Model TR515 or approved equivalent, and shall be capable of receiving baseband type monochrome or color video signals over unshielded twisted pair (UTP) telephone cables, Category 3 or better, 24 gage or heavier up to a maximum cable length of 1,500 feet (458 meters), when connected to any Northern Information Technology (NITEK) Passive Video Transceiver (or approved equivalent at the opposite end of the UTP.
- 2.2.2 Receiving video signals, as described in paragraph 2.2.1 shall mean that the active video receiver shall be capable of delivering a monochrome or color video signal of 525 lines at the maximum specified distances.
- 2.2.3 The active receiver shall be provided with a 12 V, 5 Watt DC power pack, which shall have provisions to plug directly into an AC wall outlet and shall provide two wires (2 foot minimum in length) to connect to the receiver power terminals.

UNSHIELDED TWISTED PAIR ACTIVE VIDEO RECEIVER – TR515

TECHNICAL SPECIFICATIONS

SECURITY SYSTEM

DIVISION 16 – ELECTRICAL

SECTION 16 _ _ _ - CLOSED CIRCUIT TELEVISION (CCTV) SYSTEM

PART 2 – PRODUCTS (continued)

2.2 SPECIFICATIONS (continued)

- 2.2.4 The active receiver shall provide frequency equalization by means of eight dual in-line (DIP) switches. The switches shall provide compensation for varying cable lengths from 100 to 1,500 feet, when a NITEK passive transmitter (or approved equivalent) is used. The effect of the frequency compensation shall be to both equalize and to amplify the video signal thereby providing loss compensation for video as cable length is increased.
- 2.2.5 The active receiver shall be capable of equalizing a color video signal of NTSC standard 525 lines or PAL standard 625 lines and shall deliver a baseband video signal capable of driving a 75 ohm impedance load.
- 2.2.6 The active receiver shall have built-in transient protection, with a screw connection for earth ground.
- 2.2.7 Video connection to the active receiver shall be by means of a BNC type female connector. A five screw terminal block shall provide connection to the UTP cable (2), 12 VDC power supply (2) and earth ground (1).
- 2.2.8 The active receiver shall also operate as specified in paragraph 2.2.1 when used as a receiver for any commercially available UTP equipped camera, camera enclosure and/or dome in which a Northern Information Technology, Inc. (NITEK) Model VB22 (or approved equivalent) is installed as a transmitter device.
- 2.2.9 The active receiver shall operate within specifications without causing interference or interfering with any other base band video, communication, data and/or other low-voltage signals operating in multi-twisted pair UTP cables as specified in paragraph 2.2.1.
- 2.2.10 The active receiver shall be covered by a Limited Five Year Warranty.

2.3 PERFORMANCE SPECIFICATIONS

- 2.3.1 The active receiver unit shall meet or exceed the following performance specifications:
- A. With a symmetrical and balanced composite input from the transmitter unit and using cables as specified in paragraph 2.2.1, at a cable length of 1,500 feet, the output shall be a 1 Vpp composite video signal into 75 ohms.
 - B. The receiver unit shall be capable of receiving RS170, NTSC, PAL, SECAM and CCIR video formats (color or monochrome).

UNSHIELDED TWISTED PAIR ACTIVE VIDEO RECEIVER – TR515

TECHNICAL SPECIFICATIONS

SECURITY SYSTEM

DIVISION 16 – ELECTRICAL

SECTION 16 ___ - CLOSED CIRCUIT TELEVISION (CCTV) SYSTEM

PART 2 – PRODUCTS (continued)

2.3 PERFORMANCE SPECIFICATIONS (continued)

- C. Operating frequency range: DC to 10 MHz.
- D. Input: 0.6 to 1.6 Vpp composite color or black and white video signal into 75 Ohms.
- E. Common mode rejection to be > 70 dB.
- F. Voltage requirements: 12 VDC Power Supply provided.
- G. Size: Enclosure to be Black Cylolac ABS Flame Retardent Thermoplastic with a maximum size of 1.25”h x 1.5”w x .75”d (w = 2.25” including BNC connector).
- H .Temperature: System must operate in an ambient temperature of –40 Degrees C to +85 degrees C, 0 to 98% non-condensing.